

TUPRESTIGE AQUA D



TEMPERATURE: -40°C / +120°C (-40°F / +248°F)
NORM: ISO 1307 for dimensional tolerances



Refer to guidelines for cleaning and sanitizing on [TUDERTECHNICA.COM](https://tudertechnica.com)

Premium grade low permeation delivery hose suitable for drinking water.

TUBE
IIR, black, tested in compliance with NSF/ANSI/CAN 61 Drinking Water System Components - Lead Content. Meets FDA 21 CFR 177.2600.

REINFORCEMENT
Synthetic plies.

COVER
Smooth, blue, cloth finish. Abrasion, ageing and ozone resistant

Inside diameter		Outside diameter		Vacuum		Working pressure		Burst pressure		Appr. Weight		Bending radius	
mm	in	mm	in	bar	psi	bar	psi	bar	psi	kg/mt	lbs/ft	mm	in
13	0,50	23	0,91	-	-	10	150	40	600	0,33	0,22	-	-
19	0,75	29	1,14	-	-	10	150	40	600	0,43	0,29	-	-
25	1,00	35	1,38	-	-	10	150	40	600	0,54	0,36	-	-
32	1,25	42	1,65	-	-	10	150	40	600	0,68	0,46	-	-
38	1,50	48	1,89	-	-	10	150	40	600	0,79	0,53	-	-
51	2,00	64	2,52	-	-	10	150	40	600	1,44	0,97	-	-
63,5	2,50	76,5	3,01	-	-	10	150	40	600	1,73	1,16	-	-
76	3,00	89	3,50	-	-	10	150	40	600	2,03	1,36	-	-
102	4,00	115	4,53	-	-	10	150	40	600	2,66	1,79	-	-

Data refer to ambient temperature (20°C). Other diameters, wall thickness, cover colours and pressure only on specific request.