

TUPRESTIGE CRUSH RESISTANT 16-64 TBF



Premium grade low permeation suction and delivery hose suitable for a wide range of products. Recommended for wine and spirits. Crush resistant.

TUBE

BIIR, white, phthalates free, tested in compliance with 1907/2006/CE (REACH). Meets FDA 21 CFR 177.2600, DM 21.03.73 E SEGUENTI, EUROPEAN REGLEMENT 1935/2004/CE, JAPAN-MINISTRY OF HEALTH AND WELFARE NOTICE NO.370,1959 AND NO.201,2006, 3A Sanitary Standard Class II

TEMPERATURE: -40°C / +120°C (-40°F / +248°F)

NORM: ISO 1307 for dimensional tolerances

REINFORCEMENT

Synthetic plies, thermoplastic wire helices.



COVER

Smooth, grey, abrasion, ageing and ozone resistant, cloth finish.

Refer to guidelines for cleaning and sanitizing on [TUDERTECHNICA.COM](https://tudertech.com)

Inside diameter		Outside diameter		Vacuum		Working pressure		Burst pressure		Appr. Weight		Bending radius	
mm	in	mm	in	bar	psi	bar	psi	bar	psi	kg/mt	lbs/ft	mm	in
25	1,00	37	1,46	0,7	10	16	250	64	1000	1,01	0,54	115	4,52
38	1,50	55	2,16	0,7	10	16	250	64	1000	1,54	0,82	180	7,08
51	2,00	66	2,60	0,7	10	16	250	64	1000	1,87	1,27	250	9,84
63,5	2,50	78,5	3,09	0,7	10	16	250	64	1000	2,31	2,48	320	12,59
76	3,00	92	3,62	0,7	10	16	250	64	1000	2,91	3,13	390	15,35

Data refer to ambient temperature (20 °C). Other diameters, wall thickness, cover colours and pressure only on specific request.